

# Single Phase String Inverter

SUN- 1.5 / 2.2 / 2.7 / 3 / 3.3 / 3.6 / 4 K-G03



1 MPP tracker, Max. efficiency up to 97.5%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)



Low start-up voltage of 80V

**Deye**

Stock Code: 605117.SH

Model	SUN-1.5K-G03	SUN-2.2K-G03	SUN-2.7K-G03	SUN-3K-G03	SUN-3.3K-G03	SUN-3.6K-G03	SUN-4K-G03
<b>Input Side</b>							
Max. DC Input Power (kW)	2	2.9	3.5	3.9	4.3	4.7	5.2
Max. DC Input Voltage (V)				500	550		
Start-up DC Input Voltage (V)				80			
MPPT Operating Range (V)				70~450	70~500		
Max. DC Input Current (A)				13			
Max. Short Circuit Current (A)				19.5			
No.of MPP Trackers				1			
No.of Strings per MPP Tracker				1			
<b>Output Side</b>							
Rated Output Power (kW)	1.5	2.2	2.7	3	3.3	3.6	4
Max. Active Power (kW)	1.65	2.42	2.97	3.3	3.63	3.96	4.4
Nominal Output Voltage / Range (V)	L/N/PE 220/230V (Optional)						
Rated Grid Frequency (Hz)	50 / 60 (Optional)						
Operating Phase	Single phase						
Rated AC Grid Output Current (A)	6.5	9.6	11.7	13	14.3	15.7	17.4
Max. AC Output Current (A)	7.2	10.5	12.9	14.3	15.8	17.2	19.1
Output Power Factor	0.8 leading to 0.8 lagging						
Grid Current THD	<3%						
DC Injection Current (mA)	<0.5%						
Grid Frequency Range	47~52 or 57~62 (Optional)						
<b>Efficiency</b>							
Max. Efficiency	97.3%	97.3%	97.3%	97.5%	97.5%	97.5%	97.5%
Euro Efficiency	97.1%	97.1%	97.1%	97.3%	97.3%	97.3%	97.3%
MPPT Efficiency	>99%						
<b>Protection</b>							
DC Reverse-Polarity Protection	Yes						
AC Short Circuit Protection	Yes						
AC Output Overcurrent Protection	Yes						
Output Overvoltage Protection	Yes						
Insulation Resistance Protection	Yes						
Ground Fault Monitoring	Yes						
Anti-islanding Protection	Yes						
Temperature Protection	Yes						
Integrated DC Switch	Yes						
Remote software upload	Yes						
Remote change of operating parameters	Yes						
Surge protection	DC Type II / AC Type II						
<b>General Data</b>							
Size (mm)	280W×272.5H×184D						
Weight (kg)	4.8						
Topology	Transformerless						
Internal Consumption	<1W (Night)						
Running Temperature	-25~65°C, >45°C derating						
Ingress Protection	IP65						
Noise Emission (Typical)	≤35 dB						
Cooling Concept	Natural cooling						
Max. Operating Altitude Without Derating	2000m						
Warranty	8 years						
Grid Connection Standard	VDE4105, IEC61727/62116, VDE0126, AS4777.2, CEI 0 21, EN50549-1, G98, G99, C10-11, UNE217002, NBR16149/NBR16150						
Operating Surroundings Humidity	0-100%						
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2						
<b>Features</b>							
DC Connection	MC-4 mateable						
AC Connection	IP65 rated plug						
Display	LCD1602						
Interface	RS485/RS232/Wifi/LAN						